

**Viking Paints, Inc.**  
100 W. 78<sup>th</sup> St.  
Richfield, MN 55423  
www.vikingpaints.com

Phone: 612-866-1212  
Fax: 612-866-5821  
E-mail: vikingpaints@earthlink.net

## PRODUCT & TECHNICAL DATA SHEET

|  |  |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
|--|--|--------------------|---------------|--------------------|---------|--------------------|---------|--------|--------|--------------|-----|-------------|------|--|-------|-----------------|------------|------------------|------------|----------------------|----------|-------------------|--------------|-------|--------------|
| <b><u>PRODUCT LINE</u></b>             | EXTERIOR LATEX   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| <b><u>PRODUCT NAME</u></b>             | <u>NORSEMAN EXTERIOR LATEX</u>   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| <b><u>MANUFACTURER</u></b>             | Viking Paints, Inc.  |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| <b><u>DESCRIPTION</u></b>              | <p>A premium, acrylic latex coating designed to provide maximum durability over masonry or properly primed wood surfaces.</p> <p>The pigmentation of this product gives optimum light reflectance and resistance to ultra-violet degradation. Only the finest quality raw materials are used throughout in the production of this product. This product is mainly used for exterior applications.</p>  |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| <b><u>BASIC USES</u></b>               | Exterior walls   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| <b><u>PHYSICAL DATA</u></b>            | <table><tr><td>Weight Per Gallon:</td><td>11.46 lbs/gal</td></tr><tr><td>Solids Wt./Gallon:</td><td>53.008%</td></tr><tr><td>Solids Wt./Volume:</td><td>38.403%</td></tr><tr><td>% PVC:</td><td>36.557</td></tr><tr><td>Krebs Units:</td><td>102</td></tr><tr><td>ICI POISES:</td><td>1.25</td></tr><tr><td>SPECIFIC GRAVITY (H<sub>2</sub>O=1):</td><td>1.314</td></tr><tr><td>COATING V.O.C.:</td><td>114.21 g/l</td></tr><tr><td>MATERIAL V.O.C.:</td><td>49.187 g/l</td></tr><tr><td>SOLUBILITY IN WATER:</td><td>Miscible</td></tr><tr><td>APPEARANCE RANGE:</td><td>White liquid</td></tr><tr><td>ODOR:</td><td>Minimal Odor</td></tr></table> <p>For additional information, please refer to the Safety Data Sheet.</p> | Weight Per Gallon: | 11.46 lbs/gal | Solids Wt./Gallon: | 53.008% | Solids Wt./Volume: | 38.403% | % PVC: | 36.557 | Krebs Units: | 102 | ICI POISES: | 1.25 | SPECIFIC GRAVITY (H <sub>2</sub> O=1): | 1.314 | COATING V.O.C.: | 114.21 g/l | MATERIAL V.O.C.: | 49.187 g/l | SOLUBILITY IN WATER: | Miscible | APPEARANCE RANGE: | White liquid | ODOR: | Minimal Odor |
| Weight Per Gallon:                     | 11.46 lbs/gal  |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| Solids Wt./Gallon:                     | 53.008%  |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| Solids Wt./Volume:                     | 38.403%  |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| % PVC:                                 | 36.557   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| Krebs Units:                           | 102  |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| ICI POISES:                            | 1.25   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| SPECIFIC GRAVITY (H <sub>2</sub> O=1): | 1.314  |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| COATING V.O.C.:                        | 114.21 g/l   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| MATERIAL V.O.C.:                       | 49.187 g/l   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| SOLUBILITY IN WATER:                   | Miscible   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| APPEARANCE RANGE:                      | White liquid   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| ODOR:                                  | Minimal Odor   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| <b><u>SURFACE PREPARATION</u></b>      | Clean surface, remove any peeled or loose paint, and allow surface to dry.   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| <b><u>APPLICATION</u></b>              | Apply paint to surface.  |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| <b><u>CAUTIONS</u></b>                 | Do not allow this product to freeze. Store at temperatures which will not cause exposure to near freezing conditions.  |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |
| <b><u>WARRANTY</u></b>                 | The manufacturer warrants all materials to be free from defects and will replace any material proven to be defective when applied according to our specifications -- at no cost -- within a period of one year. No other warranties are implied or intended.   |                    |               |                    |         |                    |         |        |        |              |     |             |      |  |       |                 |            |                  |            |                      |          |                   |              |       |              |