

**Viking Paints, Inc.**

100 W. 78<sup>th</sup> St.  
Richfield, MN 55423  
www.vikingpaints.com

Phone: 612-866-1212  
Fax: 612-866-5821  
E-mail: vikingpaints@earthlink.net

**PRODUCT & TECHNICAL DATA SHEET**

<b><u>PRODUCT LINE</u></b>	<u>Custom Burial Vault Coating</u>
<b><u>PRODUCT NAME</u></b>	<b><u>HLVP Clear Topcoat</u></b>
<b><u>MANUFACTURER</u></b>	Viking Paints, Inc.
<b><u>DESCRIPTION</u></b>	Water-reducible clear alkyd high-gloss base for colors & metals.
<b><u>BASIC USES</u></b>	Top coat for concrete burial vaults.
<b><u>PHYSICAL DATA</u></b>	Color: Off-Yellow Appearance: Glossy PH: 8.2-8.7 Solids by Wt.: 22.43% Solids by Volume: 19.47% Viscosity: 14 seconds #3 Zahn V.O.C.: 158.902g/l For additional information, please refer to the Safety Data Sheet.
<b><u>TECHNICAL DATA</u></b>	Dry: Has ability to accept metal powders – copper, zinc and aluminum. Has early water resistance – 24 hours.
<b><u>SURFACE PREPARATION</u></b>	Vault should already be sealed with VPI-200-YEL Yellow Sealer.
<b><u>MIXING INSTRUCTIONS</u></b>	Use as supplied or mix with colors or metal powders.
<b><u>APPLICATION</u></b>	Spray with HVLP.
<b><u>CURE SCHEDULE</u></b>	Air dry: dry to touch 1 hour. Wait 4 hours before moving vault. Wait 24 hours before shipping vault
<b><u>COVERAGE</u></b>	354 sq. ft. / gallon
<b><u>PACKAGING</u></b>	Comes in 5-gallon paints and 55-gallon drums.
<b><u>DURABILITY</u></b>	2 years above ground – not applicable below ground.
<b><u>WARRANTY</u></b>	The manufacturer warrants all materials to be free from defects and will replace any material proven to be defective when applied according to our specifications -- within a period of one year. No other warranties are implied or intended.